

Safety Data Sheet

Silicone Slip Coat II

SDS Revision Date:

10/22/2018

1. Identification

1.1. Product identifier

Product Identity Silicone Slip Coat II

Alternate Names Silicone Slip Coat II

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use See Technical Data Sheet.

Application Method See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name Commercial Maintenance Supply, Inc.
6021 TARBELL ROAD
SYRACUSE, NEW YORK 13206 USA

Emergency

CHEMTREC (USA) (800) 424-9300

Customer Service: Commercial Maintenance Supply, Inc. 315-437-3806 or 800-955-DRUM

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Aquatic Chronic 2;H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



H411 Toxic to aquatic life with long lasting effects.

[Prevention]:

P273 Avoid release to the environment.

[Response]:

P391 Collect spillage.

[Storage]:

Safety Data Sheet

Silicone Slip Coat II

SDS Revision Date:

10/22/2018

No GHS storage statements

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Dimethylsiloxane CAS Number: 0063148-62-9	50 - 75	Aquatic Chronic 2;H411	[1]
Petroleum distillates, hydrotreated light CAS Number: 0064742-47-8	25 - 50	Asp. Tox. 1;H304	[1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes

Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion

Never give anything by mouth to an unconscious person. If swallowed, do not induce vomiting. Give large quantities of water. If available give several glasses of milk. Call physician or poison control center.

4.2. Most important symptoms and effects, both acute and delayed

Overview

Eye contact: May causes eye irritation. Direct eye contact with product or mist may cause redness, tearing & stinging.

Skin contact: May cause irritation or dermatitis, defatting.

Inhalation: May cause irritation to mucus membrane.

Ingestion: May cause irritation in the digestive system, irritation, anorexia, nausea, vomiting, dyspnea, vertigo. Minor effects to the liver/kidney function.

Safety Data Sheet

Silicone Slip Coat II

SDS Revision Date:

10/22/2018

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

5. Fire-fighting measures

5.1. Extinguishing media

Dry chemical, foam or CO₂. Water may be effective for cooling, but may not be effective in extinguishment

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: By thermal oxidation degradation: carbon monoxide, carbon dioxide and other oxides may be generated.

5.3. Advice for fire-fighters

Firefighter should wear self-contained breathing apparatus and protective clothing. Use water to cool enclosed container. May form explosive mixtures with air. Vapor may travel a considerable distance to an ignition source and flashback. Container explosion may occur under fire conditions.

ERG Guide No. ----

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Precautions in case of spill: Clean up personnel must wear proper protective equipment. Ventilate area and remove all ignition sources. Dike and recover for intended use. Mop up remainder with absorbent materials. Observe all safety precautions concerning inhalation, skin, ingestion and eyes. Do not flush into sewer. Always follow local, state and federal government regulations. Immediate cleanup of any spill is recommended.

Disposal method: Dispose of in accordance with local, county, state and federal regulations.

Safety Data Sheet

Silicone Slip Coat II

SDS Revision Date:

10/22/2018

7. Handling and storage

7.1. Precautions for safe handling

Use with adequate ventilation. Avoid eye contact.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Strong oxidizing agents and corrosives.

Store in cool dry area. Keep out of reach of children. Keep closed when not in use. Vapors may travel keep away from sources of ignition such as; sparks, pilot light, static electricity and open flames. Wash thoroughly after handling or contact.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0063148-62-9	Dimethylsiloxane	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-47-8	Petroleum distillates, hydrotreated light	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	Recommended 300 ppm PEL

Carcinogen Data

CAS No.	Ingredient	Source	Value
0063148-62-9	Dimethylsiloxane	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-47-8	Petroleum distillates, hydrotreated light	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

Safety Data Sheet

Silicone Slip Coat II

SDS Revision Date:

10/22/2018

8.2. Exposure controls

Respiratory	Do not breathe vapors. Use in a well ventilated area. Use the appropriate, certified organic respirators when necessary.
Eyes	Chemical splash goggles, if used in a manner where splash may occur.
Skin	Chemical resistant aprons and gloves.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

9. Physical and chemical properties

Appearance	Pink Liquid
Odor	Characteristic
Odor threshold	Not Measured
pH	Not Measured
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	Not Measured
Flash Point	> 203° F
Evaporation rate (Ether = 1)	Not Measured
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Measured Upper Explosive Limit: Not Measured
Vapor pressure (Pa)	Not Measured
Vapor Density	Not Measured
Specific Gravity	Not Measured
Solubility in Water	Not Measured
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
Density	7.58 lb/gal

9.2. Other information

No other relevant information.

Safety Data Sheet

Silicone Slip Coat II

SDS Revision Date:

10/22/2018

10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Excessive heat and open flame.

10.5. Incompatible materials

Strong oxidizing agents and corrosives.

10.6. Hazardous decomposition products

By thermal oxidation degradation: carbon monoxide, carbon dioxide and other oxides may be generated.

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Dimethylsiloxane - (63148-62-9)	No data available	No data available	No data available	No data available	No data available
Petroleum distillates, hydrotreated light - (64742-47-8)	> 5,000.00, Rat - Category: NA	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable

Safety Data Sheet

Silicone Slip Coat II

SDS Revision Date:

10/22/2018

Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

12. Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

Air: This product is a high molecular weight liquid polymer which has a very low vapor pressure (<1 mm Hg). As a result it is unlikely to become an atmospheric containment unless generated as an aerosol.

Water: This product has very low solubility (<100 ppb). As it has a specific gravity of < 1, if discharged to water, it will initially form a surface film. AS the product is non volatile and has a high binding affinity for particulate matter, it will absorb to particulates and sediment out.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Dimethylsiloxane - (63148-62-9)	3.16, Ictalurus punctatus	44.50, Daphnia magna	Not Available
Petroleum distillates, hydrotreated light - (64742-47-8)	45.00, Pimephales promelas	4,720.00, Dendronereides heteropoda	Not Available

12.2. Persistence and degradability

Degradation: This product, polydimethylsiloxane, degrades in soil abiotically to form smaller molecules. These in turn are either biodegraded in soil or volatilized into the air where they are broken down in the presence of sunlight. Under appropriate conditions, the ultimate degradation products are inorganic silica, carbon dioxide and water vapor. Due to the very low solubility of this product, standard OECD protocols for ready and inherent biodegradability are not suitable for measuring the biodegradability of this product. The product is removed >80% during the sewage treatment process.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

Soil: If discharged to surface water, this product will bind to sediment. If discharged in effluent to a waste water treatment plant, the product is removed from the aqueous phase by binding to sewage sludge. If the sewage sludge is subsequently spread on soil the silicone product is expected to degrade.

Safety Data Sheet

Silicone Slip Coat II

SDS Revision Date:

10/22/2018

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

Environmental Effects : Toxicity to Water Organisms: Based on analogy to similar materials this product is expected to exhibit low toxicity to aquatic organisms.

Toxicity to Soil Organisms: Experiments show that when sewage sludge containing polydimethylsiloxane is added to soil, it has no effect on soil micro-organisms, earthworms or subsequent crops grown in the soil.

Bioaccumulation: This product is a liquid and is a high molecular weight polymer. Due to its physical size it is unable to pass through, or be absorbed by biological membranes. This has been confirmed by testing or analogy with similar products.

Fate and Effects in Waste Water Treatment Plants

This product or similar products has been shown to be non-toxic to sewage sludge bacteria.

Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC 50) High Medium Low Acute Aquatic Toxicity (mg/L) ≤ 1 > 1 and ≤ 100 > 100 Acute Terrestrial Toxicity ≤ 100 > 100 and ≤ 2000 > 2000 This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable
14.5. Environmental hazards			
IMDG	Marine Pollutant: Yes (Dimethylsiloxane)		
14.6. Special precautions for user	No further information		

Safety Data Sheet Silicone Slip Coat II

SDS Revision Date:

10/22/2018

15. Regulatory information

Regulatory Overview

The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Toxic Substance Control Act (TSCA)

All components of this material are either listed or exempt from listing on the TSCA Inventory.

WHMIS Classification



Fire: 1
Sudden Release of Pressure: No
Reactive: 0
Immediate (Acute): No
Delayed (Chronic): No

US EPA Tier II Hazards

EPCRA 311/312 Chemicals and RQs:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%) :

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Pennsylvania RTK Substances (>1%) :

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Safety Data Sheet

Silicone Slip Coat II

SDS Revision Date:

10/22/2018

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

THE INFORMATION IN THIS DOCUMENT IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. THIS INFORMATION AND PRODUCT ARE FURNISHED ON THE CONDITION THAT THE PERSON RECEIVING THEM SHALL MAKE HIS OWN DETERMINATION AS TO THE SUITABILITY OF THE PRODUCT FOR HIS PARTICULAR PURPOSE AND ON THE CONDITION THAT HE ASSUME THE RISK OF HIS USE THEREOF.

End of Document